















FIGURE 4

```
405
                   </switch>
                  <switch name="idcsw2" ip="15.4.93.43" type="rack" >
<port name="J3" linksTo="00:D0:B7:06:E4:98" > </port>
<port name="J4" linksTo="00:D0:B7:20:22:86" > </port>
<port name="J4" type="trunk" trunkname="Tx60" linksTo="idcsw48Txk0" > </port>
<port name="J6" type="trunk" trunkname="Tx60" linksTo="idcsw48Txk0" > </port>
 410
                  <switch name="idcsw3" ip="15.4.93.44" type="edge" >
<port name="01" type="trunk" trunkname="Trk0" linksTo="idcsw5$Trk0"> </port>
<port name="02" type="trunk" trunkname="Trk0" linksTo="idcsw5$Trk0"> </port>
<port name="03" type="trunk" trunkname="Trk1" linksTo="idcsw1$Trk0"> </port>
<port name="04" type="trunk" trunkname="Trk1" linksTo="idcsw1$Trk0"> </port>
<port name="04" type="trunk" trunkname="Trk1" linksTo="idcsw1$Trk0"> </port></port></port>
 415
                 <switch name="idcsw4" ip="15.4.93.45" type="edge">

<pre
420
                  </switch>
                 425
                 </switch>
              <host name='idc1" >
  <interface name='1" mac='00:D0:B7:06:E7:95" linksTo='idcsw1$J4"> </interface>
  <interface name='2" mac='00:D0:B7:20:32:86" linksTo='idcsw2$J4"> </interface>
  </oobt>
435
                <host name="idc2" >
<interface name="1" mac="00:D0:B7:06:E7:5C" linksTo="idcswl#JJ"> </interface
<interface name="2" mac="00:D0:B7:06:E4:9B" linksTo="idcsw2#JJ"> </interface>
440
             <interf
</host>
```

tell life in the state of the s